

Entrance Doors Specification

Component	Materials	Typical Size (width x depth/height)
Frames	Treated laminated redwood with solid rebates and horns unless otherwise specified.	92mm x 70mm
Threshold	Hardwood (Sapele)	145mm x 57mm
Door	Vertical grain, clear Douglas Fir	
Door Stiles	Vertical grain, clear Douglas Fir	110-120 mm x 54mm
Door Rails	Vertical grain, clear Douglas Fir	190- 220mm x 54mm
Panels (flush and raised and fielded)	Birch Faced Plywood / Solid Timber	24mm
Glass	Clear low E Softcoat - Toughened	4mm- 16mm – 4mm
Muntins	Vertical grain, clear Douglas Fir	95mm
Hinges	British made butt hinges with washers (Not cheap case iron imports)	67mm x 100mm
Lock	5-lever mortice deadlock with night latch as standard with option for multipoint locks to be fitted.	
Draught Seals	Double Aquamac 21 weatherseal used in frame	

Note: please check all specifications before ordering.

<u>Bespoke Specifications*</u>
Thresholds are available in oak or hardwood
Supplied with mobility threshold
Supplied without thresholds if stone threshold is to be used
Multipoint lock
Hinge bolts
Letterplate
Weatherboard
Laminated glass
Clerestory (fan lights)
Ironmongery bronze, brass, chrome and satin chrome
Staff beaded rebate
Extended cill
Galvanised water bar
Hung-opposite hand
Horns trimmed
Door thickness can be varied from 44-57mm
Diminished stiles
Head drip
3 coat finish

*Any of the above must be agreed at time of order.