

Sliding/ Stacking and Bi-folding Doors

Component	Materials	Typical Size
Frames	Treated laminated redwood with solid rebates and horns unless otherwise specified.	Sliding 150mm x 57mm Sliding stacking 158mm x 57mm Bi-folding 158mm x 57mm
Threshold	Hardwood (Sapele)	Varies to suit requirements
Door	Vertical grain, clear Douglas Fir	54mm thick (Cill height and projection varies according to requirements)
Door jamb	Vertical grain, clear Douglas Fir	110mm x 54mm
Panels (flush and raised and fielded)	Birch Faced Plywood / Solid Timber	24mm
Glass	Clear low E Softcoat - Toughened	4mm- 16mm – 4mm
Sliding door locks & ironmongery	Silver anodised aluminium finished lift and slide system with a multi-point lock.	n/a
Stacking and bi-folding door locks and ironmongery	Hafele Centor E3 folding door hardware system including hinges. Multi-point espagnolette mechanism and handle as before.	n/a

Note: please check all specifications before ordering.

<u>Bespoke Specifications*</u>
Hardwood Thresholds available in Oak Weather drip Toughened laminated glass, low E, Argon Ironmongery satin silver and satin brass as standard Door adjuster incorporated in the hinges Trickle vent Head drip Folding doors outward opening as standard 3 Coat finish

***Any of the above must be agreed at time of order.**