

Timber French Doors Specification

Component	Materials	Typical Size (width x depth/height)
Frames	Treated laminated redwood with solid rebates and horns unless otherwise specified.	92mm x 50 / 70mm
Threshold	Hardwood (Sapele)	145mm x 57mm
Door	Vertical grain, clear Douglas Fir	
Door Stiles	Vertical grain, clear Douglas Fir	110mm x 54mm
Door Rails	Vertical grain, clear Douglas Fir	Top rail - 95mm x 54mm Mid and bottom rail - 190mm x 54mm
Panels (flush and raised and fielded)	Birch Faced Plywood / Solid Timber	24mm
Glass	Clear low E Softcoat - Toughened	4mm- 16mm – 4mm
Hinges	British made projection / butt hinges with washers (not cheap cast imports)	100mm x 125mm / 100mm x 67mm
Lock	Multi-point espagnolette locking mechanism with Stella or Scroll standard door handles and euro-cylinder to suit.	
Draught Seal	Double Aquamac 21 weatherseal used in both frame and plant on staff beads	

Note: please check all specifications before ordering.

<u>Bespoke Specifications*</u>
<p>Hardwood Thresholds are available in oak Supplied without thresholds if stone threshold is to be used Supplied with mobility threshold Hinge bolts Weather board Weather drip (frame head) Plant-on glazing bead Solid ovolo/splay rebate Laminated glass, low E, Argon Clerestory (fan lights) Ironmongery chrome, brass, bronze and satin chrome Bi-folding doors have incorporated in the stiles our unique door adjuster Trickle vents Head drip Inward opening Single leaf only Weather drip 3 Coat finish</p>

***Any of the above must be agreed at time of order.**